




**Rack PDU, Basic, Zero U, 22kW, 400V,
(6) C19 & (3) C13**

Part Number: AP7555



Output

Nominal Output Voltage	230V	
Maximum Total Current Draw per Phase	32A	
Output Connections	(3) IEC 320 C13 (6) IEC 320 C19	
Overload Protection	Yes	

Input

Nominal Input Voltage	400V 3PH
Input Frequency	47 - 63 Hz
Input Connections	IEC 309 32A 3P+N+PE
Cord Length	1.83 meters
Number of Power Cords	1
Acceptable Input Voltage	200-250 VAC
Maximum Line Current per phase	32A
Maximum Input Current per phase	32A

Physical

Net Weight	4.75 KG
Maximum Height	927.00 mm
Maximum Width	55.00 mm
Maximum depth	88.00 mm
Shipping Weight	6.25 KG
Shipping Height	1054.00 mm
Shipping Width	286.00 mm
Shipping Depth	70.00 mm
Color	Black

Environmental

Operating Environment	-5 - 45 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	CE,GOST,VDE
Standard Warranty	2 years repair or replace

*With Tax/VAT

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)