




## Rack PDU, Basic, Zero U, 11 kW, 230V, (36) C13 & (6) C19

Part Number: AP7557



### Output

Nominal Output Voltage	230V	
Maximum Total Current Draw per Phase	16A	
Output Connections	(36) IEC 320 C13 (6) IEC 320 C19	
Overload Protection	No	

### Input

Nominal Input Voltage	400V 3PH
Input Frequency	47 - 63 Hz
Input Connections	IEC 309 16A 3P+N+PE
Cord Length	0.91 meters
Number of Power Cords	1
Maximum Input Current per phase	16A

### Physical

Net Weight	5.45 KG
------------	---------

Maximum Height	1619.00 mm
Maximum Width	56.00 mm
Maximum depth	44.00 mm
Shipping Weight	8.86 KG
Shipping Height	2134.00 mm
Shipping Width	152.00 mm
Shipping Depth	127.00 mm
Color	Black

## Environmental

Operating Environment	-5 - 45 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters

## Conformance

Regulatory Approvals	C-tick,CCC,CE,GOST,MIC,Queensland Australia,VDE
Standard Warranty	2 years repair or replace

\*With Tax/VAT

[Copyright](#) © American Power Conversion Corp., all rights reserved  
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)