



**Rack  
PDU  
Extender,  
Basic,  
2U, 32A,  
230V, (4)  
IEC C19**



**Part  
Number:**  
AP7585

## Output

Nominal Output Voltage	230V
Maximum Total Current Draw per Phase	32A
Output Connections	(4) IEC 320 C19

## Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	Hard Wire 3-wire
Cord Length	8.53 meters
Number of Power Cords	1
Maximum Input Current per phase	32A
Load Capacity	7360 VA

## Physical

Net Weight	4.09 KG
Maximum Height	89.00 mm
Maximum Width	437.00 mm
Maximum depth	89.00 mm
Shipping Weight	5.00 KG
Shipping Height	152.00 mm
Shipping Width	521.00 mm

Shipping Depth	521.00 mm
Color	Black

## Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

## Conformance

Regulatory Approvals	CE,GOST,VDE
Standard Warranty	2 years repair or replace

\*With Tax/VAT

[Copyright](#) © American Power Conversion Corp., all rights reserved  
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)