



**Rack
PDU
Extender,
Basic,
2U, 32A,
230V, (4)
IEC 309-
32
Part
Number:
AP7586**



Output

Nominal Output Voltage	230V
Maximum Total Current Draw per Phase	32A
Output Connections	(4) IEC 309

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	Hard Wire 3-wire
Cord Length	9 meters
Maximum Input Current per phase	32A
Load Capacity	7360 VA

Physical

Net Weight	4.09 KG
Maximum Height	89.00 mm
Maximum Width	437.00 mm
Maximum depth	89.00 mm
Shipping Weight	5.00 KG
Shipping Height	152.00 mm
Shipping Width	521.00 mm
Shipping Depth	521.00 mm

Color	Black
-------	-------

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	CE,VDE
Standard Warranty	2 years repair or replace

All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners. Specifications are subject to change without notice.