



**Rack PDU, Basic, 1U, 16A, 208&230V, (10)
C13 & (2)C19**
Part Number: AP9559



Output

Nominal Output Voltage	120V,208V,230V
Maximum Total Current Draw per Phase	16A
Output Connections	(10) IEC 320 C13 (2) IEC 320 C19
Always on Outlets	12
Overload Protection	No



Input

Nominal Input Voltage	120V,208V,230V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C20
Cord Length	2.5 meters
Acceptable Input Voltage	90-250 VAC
Maximum Line Current per phase	16A
Maximum Input Current per phase	16A
Load Capacity	3680 VA

Physical

Net Weight	0.98 KG
Maximum Height	44.00 mm
Maximum Width	447.00 mm
Maximum depth	57.00 mm

Available from: www.allteq.com.au

Shipping Weight	2.36 KG
Shipping Height	165.00 mm
Shipping Width	483.00 mm
Shipping Depth	152.00 mm
Color	Black

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	CE,GOST,VDE,Victoria
Standard Warranty	2 years repair or replace

All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners. Specifications are subject to change without notice.