



Rack PDU, Basic, Zero U, 10A,230V, (15)C13
Part Number: AP9568



Output

Nominal Output Voltage	208V,230V	
Maximum Total Current Draw per Phase	10A	
Output Connections	(15) IEC 320 C13	

Input

Nominal Input Voltage	208V,230V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C14
Cord Length	1.98 meters
Acceptable Input Voltage	200-240 VAC
Maximum Input Current per phase	10A
Load Capacity	2300 VA

Physical

Net Weight	2.00 KG
Maximum Height	610.00 mm
Maximum Width	44.00 mm
Maximum depth	44.00 mm
Shipping Weight	2.73 KG
Shipping Height	648.00 mm
Shipping Width	178.00 mm
Shipping Depth	152.00 mm

Color	Black
-------	-------

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	cUL Recognized,CE,CSA,GOST,Queensland Australia,UL 1363,UL Recognized,VDE
Standard Warranty	2 years repair or replace

All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners. Specifications are subject to change without notice.