




**Rack
PDU,
Basic,
Zero U,
16A,
208/230V,
(15) C13
Part
Number:
AP9572**



Output

Nominal Output Voltage	120V,208V,230V
Maximum Total Current Draw per Phase	16A
Output Connections	(15) IEC 320 C13 
Always on Outlets	15

Input

Nominal Input Voltage	120V,208V,230V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C20
Cord Length	2.5 meters
Maximum Line Current per phase	16A
Maximum Input Current per phase	16A
Load Capacity	3680 VA

Physical

Net Weight	2.00 KG
Maximum Height	620.00 mm
Maximum Width	44.00 mm
Maximum depth	44.00 mm
Shipping Weight	2.73 KG
Shipping Height	638.00 mm

Shipping Width	168.00 mm
Shipping Depth	146.00 mm
Color	Black

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	cUL Listed,CE,CSA,Queensland Australia,UL 60950,UL Listed,VDE
Standard Warranty	2 years repair or replace

All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners. Specifications are subject to change without notice.