

## Smart-UPS

SUA1000RMI2U

# APC Smart-UPS 1000VA USB & Serial RM 2U 230V



APC Smart-UPS, 670 Watts / 1000 VA, Input 230V / Output 230V, Interface Port DB-9 RS-232, SmartSlot, USB, Rack Height 2 U

**Includes:** CD with software, Rack Mounting brackets, Rack Mounting support rails, Smart UPS signalling RS-232 cable, USB cable, User Manual

**Standard Lead Time:** Usually in Stock

## Output

Output Power Capacity	670 Watts / 1000 VA
Max Configurable Power	670 Watts / 1000 VA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Crest Factor	up to 5 : 1
Waveform Type	Sine wave
Output Connections	(4) IEC 320 C13



(2) IEC Jumpers

## Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 280V
Input voltage adjustable range for mains operation	151 - 302V

## Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3 hour(s)
Replacement battery cartridge	<a href="#">RBC23</a>
RBC™ Quantity	1
Typical Backup Time at Half Load	31.6 minutes (335 Watts)
Typical Backup Time at Full Load	9.1 minutes (670 Watts)

## Communications & Management

Interface Port(s)	DB-9 RS-232, SmartSlot, USB
Available SmartSlot™ Interface Quantity	1
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional

## Surge Protection and Filtering

Surge energy rating	480 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

Maximum Height	89.00 mm
Maximum Width	432.00 mm
Maximum depth	457.00 mm
Rack Height	2U
Net Weight	28.18 KG
Shipping Weight	31.45 KG
Shipping Height	254.00 mm
Shipping Width	594.00 mm
Shipping Depth	603.00 mm
Color	Black
Units per Pallet	16.00

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	36 dBA
Online Thermal Dissipation	89.00 BTU/hr

## Conformance

Regulatory Approvals	C-tick,EN 50091-1,EN 50091-2,GOST,VDE
----------------------	---------------------------------------

Standard Warranty	2 years repair or replace
-------------------	---------------------------

\*Except where noted, all prices are Estimated Resale Price (ERP) - With Tax/VAT. Pricing in other locations and sites may vary.

\*\*The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.