



# Allteq Pty Limited

(ABN: 30 093 716 922)

**On-Line  
Superstore**

Telephone: 61-2-9953 3295  
Facsimile: 61-2-8969 6806  
Email: sales@allteq.com.au  
Web: http://www.allteq.com.au

## CANON LBP3300 MONO LASER PRINTER SPECIFICATIONS



<b>Machine Type:</b>	Desktop laser printer
<b>Printing Speed<sup>^</sup>:</b>	21 ppm in black (A4 size paper)
<b>Duplexing:</b>	Automatic as standard
<b>Resolution:</b>	600 x 600 dpi (up to 2400 x 600 dpi equivalent with Automatic Image Refinement)
<b>Method of Fixing:</b>	On Demand Fixing System
<b>Warm-up Time:</b>	0 second
<b>First Print Out Time:</b>	less than 9 seconds
<b>Printing Language:</b>	CAPT (Canon Advanced Printing Technology)
<b>Memory:</b>	8Mb using Canon's unique SCoA compression technology (no additional memory required)
<b>Paper Handling:</b>	Input tray: 250 sheet paper cassette (64 gsm), 1 sheet manual feed
<b>- Output tray:</b>	Face-down 100 sheets max.(64 gsm)
<b>Toner Cartridge:</b>	308 (approx. 2,500 pages at 5% toner coverage on A4 page), 308 II (approx 6,000 pages)
<b>Paper/Media Type:</b>	Plain paper (64-163 gsm), thick paper, transparencies, labels, envelopes
<b>Paper Size:</b>	A4, B5, A5, Legal, Letter, Envelope (C5, COM10, DL, Monarch)
<b>Interface:</b>	Universal Serial Bus (USB 2.0)
<b>Supported OS:</b>	Windows 98/Me/2000/XP
<b>Weight:</b>	Approx. 11.0 kg (excl. cartridge)
<b>Power Source:</b>	AC 200 - 240V, 50 - 60Hz
<b>Power Consumption:</b>	Max: approx. 806W
<b>- Average Operation:</b>	approx. 436W
<b>- Standby:</b>	approx. 4W
<b>Dimensions :</b>	370 x 258 x 376 mm (W x D x H)
<b>Noise<sup>^^</sup>:</b>	Operation: approx. 53dB or less
<b>- Standby:</b>	background noise level
<b>Network:</b>	Network printing with optional network card NB-C1
<b>Included As Standard:</b>	LASER SHOT LBP 3300, toner cartridge 308, User Software CD-ROM, Getting Started Guide, Power cord, Paper cassette with cover

<sup>^</sup>Print speed may vary with the content of the document and the processing speed of the host computer.:

<sup>^^</sup>Noise rating number based on ISO9296: