



MC160n

Key specifications

Print resolution 1200 x 600dpi

RAM Standard: 128MB

Print Speed 5ppm colour , 20ppm mono

Full specifications

Print

Time to first print 14 seconds mono, 23 seconds colour

Warm up time up to 35 seconds from power save

Processor speed 120MHz

Print resolution 1200 x 600dpi

Printer language Host-based printing system

OS Compatibility Windows 2000 / 2003 x64 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2008 / Server 2008 x64 / Vista / Vista x64; Mac OS X 10.3.0 - 10.5.7

Print Speed 5ppm colour , 20ppm mono

Scan

Scan resolution 600 x 600dpi

Document input 35-sheet Automatic Document Feeder (ADF), flatbed scanner

Scan to FTP, USB memory stick, E-mail, TWAIN, SMB

PDF, TIFF, JPEG

LDAP, 220 E-mail address, 30 FTP or SMB address

RJ11 x 2 (Line/Tel), PSTN, PBX Line

Available from: Allteq Pty Ltd - <http://www.allteq.com.au>

ITU-T G3(Super G3) 33.6kbps, 3 seconds/page

Up to 20 groups

Hi-Speed USB 2.0 and 10/100Base-TX Ethernet

Template Manager2, OKI LPR, TWAIN driver, Setup Utility, Scanner Utility, Fax printer driver

Tray 1: 200 sheets of 80gsm; ADF: 35 sheets of 80gsm; Optional 2nd tray: 500 sheets of 80gsm

Copy

First copy out 23 seconds mono, 52 seconds colour

Copy speed Up to 20cpm mono and up to 5cpm colour

Copy resolution Up to 600 x 600dpi;

Reduction/Enlargement Zoom 50-200%

Maximum copies 99 copies

Fax/SMS

Speed dials 220 speed dials

Fax memory 6MB (approx. 384 pages transmit and receive)

Memory

RAM Standard: 128MB

Paper Handling (MFP)

Paper size Tray 1: A4, A5, B5, letter, legal, custom size (92 - 216mm x 184 - 356mm); ADF: A4, letter, legal, custom size (140 - 216mm x 149 - 356mm); Optional 2nd tray: A4; Optional Duplex: A4

Paper weight Tray 1: 60 to 209gsm; ADF: 50 to 110gsm; Optional 2nd tray: 60 to 90gsm; Optional duplex: 60 to 90gsm

Paper output 100 sheets face down

Operating Conditions

Temperature/Humidity 10°C to 35°C (15°C to 25°C recommended) / 15% to 85% RH (35% to 70% RH recommended)

Storage -10°C to 40°C / 10% to 90% RH

Noise Operating: 55dB(A) or less, Standby: 38dB(A) or less

Power Requirements (MFP)

Power supply Single phase 220 to 240VAC +/-10%, frequency 50-60Hz +/- 2Hz

Power consumption Typical 560W, Peak 1060W, Idle 200W (average), Power save <14W

Physical

Size (HxWxD) 432 x 405 x 427 mm

Weight 20.8kg approx

Available from: Allteq Pty Ltd - <http://www.allteq.com.au>

Performance

Duty cycle(max.pages/month): Maximum: 35,000 pages/month; Average: 500 - 2,000 pages/month

Warranty

Warranty 1 year warranty

Oki Data Australia Pty Ltd • Head Office • 146 O'Riordan Street • Mascot NSW 2020 • Australia • Tel: 1800 800 140 • Fax: 02 9667 7333